



## ANATOMICALLY CONTOURED

With Low-Profile Fixation

## DISTAL LATERAL FIBULAR PLATES

Available with 2, 4, 6, 8, 10, 12, 14, 16, 18, and 20 holes in both right and left configurations (Use 2.7mm, 3.5mm and 4.0mm screws).



Distal end, with a thin profile, is rounded to minimize soft tissue irritation



## **Product Information**

Distal Fibular Plates: Stainless Steel

For use with:

- Periarticular 3.5mm Cortical Screws with 2.7mm head, self-tapping\*
- 2.7mm Mini Fragment Cortical Screws
- Forte® Distal Radial Plate System 4.0mm partially or fully threaded Cancellous Screws



## **REDUCED PROFILE SCREWS**

The head size of the Periarticular screws has been reduced significantly to create a nearly flush profile when used with a plate or independently.

DISTAL LATERAL FIBULAR PLATE						
Left	Right	Plate Holes	Length			
2347-18-02	2347-17-02	2	51mm			
2347-18-04	2347-17-04	4	73mm			
2347-18-06	2347-17-06	6	94mm			
2347-18-08	2347-17-08	8	115mm			
2347-18-10	2347-17-10	10	135mm			
2347-18-12	2347-17-12	12	156mm			
2347-18-14	2347-17-14	14	177mm			
2347-18-16	2347-17-16	16	198mm			
2347-18-18	2347-17-18	18	219mm			
2347-18-20	2347-17-20	20	239mm			

Profile	Thickness	Width
Fiulle	THICKHESS	vviutii
Distal Segment	1.0mm	13.5mm
Shaft	2.5mm	9.0mm

SCREW ANGULATION				
Screw Type	Shaft Angulation (Dual Compression Slot)		Head Ang (Round	
	Longitudinal	Transverse	Longitudinal	Transverse
2.7mm Cortical Screw	41°	19°	85°	22°
3.5mm Cortical Screw (w/2.7mm Head)*	37°	15°	78°	19°

BONE SCREW OPTIONS					
Screw	Cat No.	Length Options (mm)			
2.7mm Cortical Screws,	4827-mm-01	6, 7, 8, 9, 10, 12, 14, 16, 18, 20, 22, 24, 26,			
Self-Tapping		28, 30, 32, 34, 36, 38, 40, 42, 44, 45, 46, 48,			
		50, 52, 54, 55, 56, 58, 60, 65, 70			
3.5mm Cortical Screws	2348-mm-35	8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32,			
with 2.7mm Head, Self-Tapping*		34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56,			
		58, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110			
Forte 4.0mm Partially Threaded	2480-mm-40	10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32,			
Cancellous Screws		34, 36, 38, 40			
Forte 4.0mm Fully Threaded	2480-mm-41	10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32,			
Cancellous Screws		34, 36, 38, 40			

For use with the following instrument sets:

- Periarticular 2.7mm/3.5mm/4.0mm Screw and Instrument Tray #2348-000-00
- Mini and Small Fragment Instrument and Implant Sets
- Fibular Plate Case #2348-40
- Fibular Plate Standard Set #2347-000-06 (Includes; 4, 6, 8 Holes left and right Distal Lateral and Distal Posterior/Lateral Fibular Plates)
- Fibular Plate Expanded Set #2347-000-07 (Includes all Fibular Plates)
- \* For use with Mini Fragment Depth Gauge.



For more information about the Periarticular Plating System, contact your Zimmer representative, or visit us at www.zimmer.com.

